FloorFighter 12mm Acoustical Floor Underlayment



FloorFighter 12mm floor underlayment is made from recycled rubber tires. FloorFighter is used under floated or double glued hardwood, marble & stone flooring & carpet flooring. FloorFighter can also be used under lightweight concrete topping. FloorFighter is excellent for use in lightweight wood frame construction due to its weight & mass. FloorFighter is 1/2" thick and comes in rolls 4' x 25' (100 sq ft rolls)



Typical uses include; apartments, homes, condos, schools, hospitals and any areas where reduction from structural impact noise through the floor to ceiling assembly is required. **FloorFighter** underlayment can be installed over concrete, gypsum topping and structural sound plywood sub floors.



- 92% recycled content, qualifies for up to 5 Leed Points
- IIC rating 50+
- Easy to install, 4' x 25' rolls
- Sound control underlay for Tile, Stone, Hardwood & Carpet

Product Data:

Description Made from 92% recycled SBR (Styrene-Butadiene Rubber) tire rubber

Nominal thickness 12mm

Density (ASTM D-792 43 lbs cubic ft

Standard width 48" wide Roll length 25' long

Weight 2.00 lbs per sq ft

Hardness A Shore- 40-55

Durometer



Acoustics performance on back page



FloorFighter 12mm Acoustical Testing

Description	Detail	IIC / FIIC Rating
12mm FloorFighter Floated Engineered hardwood over 12mm FloorFighter over 6" slab		Δ 23
12mm FloorFighter Floated Engineered hardwood over 12mm FloorFighter over 1 ½" gypsum topping over 16" TJI – 24 centers RC1 channel – 1 layer 5/8 GWB		IIC 57
12mm FloorFighter 3/" Marble flooring bonded with thin set to 12mm FloorFighter glued to 8" slab		FIIC 55

