

FABRIC PANEL DATASHEET



Fabric Panel Acoustical Wall & Ceiling Panels by NetWell are designed to solve your acoustical needs while enhancing the aesthetic look of your space. With a variety of options to choose from including sizes, shapes, fabrics and colors it is easy to create the perfect solution for your reverberation sound problems.

FEATURES:

- High-quality, economical, multi-purpose panels
- Excellent acoustical performance
- Class A fire rated
- Standard, designer or C.O.M fabric
- Various mounting options
- Custom sizes and shapes

APPLICATIONS:

- Schools/universities
- Auditoriums
- Houses of worship
- Office spaces
- Theaters/studios
- Multi-purpose rooms
- Conference rooms







SPECIFICATIONS:

Visit www.controlnoise.com or call 1.800.638.9355



SIZING

All panels are custom made with standard sizes up to 4' x 10' with thicknesses ranging from 1/2" to 4". Please inquire for panels larger than 4' x 10'.

FINISHES

Guilford of Maine FR701-2100 is the industry standard. Hundreds of approved decorative fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Maharam, Designtex and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

EDGE DETAILS

A chemically hardened edge comes standard on all panels unless otherwise requested.










MOUNTING OPTIONS







ACOUSTICAL PERFORMANCE

| 1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies | | | | | | | |
|---|------|------|------|------|------|------|------|
| Frequency (Hz) | 125 | 250 | 500 | 1K | 2K | 4K | NRC |
| 1/2" Thick | 0.12 | 0.48 | 0.71 | 0.77 | 0.71 | 0.58 | 0.65 |
| 1" Thick | 0.13 | 0.24 | 0.77 | 1.08 | 1.15 | 1.07 | 0.80 |
| 2" Thick | 0.22 | 0.81 | 1.24 | 1.30 | 1.21 | 1.16 | 1.15 |
| 3" Thick | 0.49 | 1.03 | 1.29 | 1.34 | 1.23 | 1.17 | 1.20 |

Tested as Type "E" Mounting







