



Whisperib

Environmental sustainable, Acoustical Wallcovering

A socially responsible, eco-friendly wallcovering engineered from 100% solution dyed fibers, with *recycled* content, needlebonded into a continuous structure, then finished with a heatset, latex back to ensure fiber lock. This material is soft, flexible and acoustically absorbent, yet suitable for high-traffic areas. Its “self-healing” nature makes it ideal for Tackable walls while its excellent pill/fuzz resistance makes it Velcro compatible.

Specifications

Construction:	Needlebond
Pattern:	Single Rib
Fiber:	Post Industrial; Polyester/Polypropylene Blend
Total Weight:	30.0 oz. Ln. yd.
Roll Size (W x L):	54" x 24 Ln. yd. (w x l)
Packaging:	“Crush-Proof” Box

Properties

Test Method

Flammability

NFPA – 265	Passes
UBC 8-2 Corner Burn	Passes
ASTM E-84 Tunnel Test Sec. X 1.10.1	Class A

Acoustical

ASTM C-423-84A	
Gypsum Board	NRC .20
Acoustic Board	NRC .60

Colorfast

AATCC-165	
Wet Crocking	5; No Stain
Dry Crocking	4-5; Slight Stain

Electrostatic

AATCC-134	0.2 kv
-----------	--------

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT FURNISHED HEREUNDER OTHER THAN AT THE TIME OF DELIVERY IT SHALL BE OF THE QUALITY AND SPECIFICATION STATED HEREIN. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED, AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE, ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. ANY RECOMMENDATIONS MADE BY THE SELLER CONCERNING THE USES OR APPLICATIONS OF SAID PRODUCT ARE BELIEVED RELIABLE AND SELLER MAKES NO WARRANTY OF RESULTS TO BE OBTAINED. IF THE PRODUCT DOES NOT MEET CROSSPOINT'S CURRENT PUBLISHED SPECIFICATIONS, AND THE CUSTOMER GIVES NOTICE TO CROSSPOINT FABRICS BEFORE INSTALLING THE PRODUCT, CROSSPOINT FABRICS WILL REPLACE THE PRODUCT WITHOUT CHARGE OR REFUND THE PURCHASE PRICE.