

## QB BAFFLE Quilted Fiberglass Baffle

Netwell's QB BAFFLE quilted fiberglass baffle features a durable vinyl-coated-fiberglass-cloth facing quilted to two-inch thick fiberglass batting. They are available in a variety of colors and stitch patterns. Standard size is 4'x2' with 2 brass grommets on one four foot side.

- Class A (or 1) per ASTM E84
- NRC 7.45 sabins per baffle
- Available colors: gray, white, black, or tan
- Flame spread 17.66
- Smoke density 22.75



#### **Applications:**

Used when you need to introduce soft, sound absorptive materials in hard reflective environments in order to reduce the reverberant noise energy in a room. Typical uses include in industrial plants, gymnasiums, auditoriums, and warehouses.

#### **Product Data**

**Description** Vinyl coated fiberglass cloth quilted to both sides of a two-inch thick

fiberglass batting.

Nominal thickness 2.0"

Temperature range -20° to +180° F

Standard width48"Standard length24"Weight of Baffle4.0 lbs.

# **Acoustical Performance:**

### Sound Absorption coefficients-Sabins per Baffle

	OCTAVE BAND FREQUENCIES (Hz)						
Product	125	250	500	1000	2000	4000	NRC
QB BAFFLE	.91	6.07	8.25	8.88	6.65	5.58	7.45

ASTM C 423-81