



BLUSH

ACOUSTICAL WALL & CEILING PANELS

NetWell Noise Control sound panels with BLUSH finish are the perfect solution where a traditional fabric finish is not desired. The acoustically transparent, paintable finish blends well with finished drywall to create a space absent of echo and reverberation. Rather than a textured finish of fabric, BLUSH panels provide for an understated, more discreet acoustic finish within a space.

BLUSH finish by NetWell Noise Control is part of a Class A rated system tested per ASTM E-84. In standard Signature White or any Pantone color, NetWell Noise Control BLUSH finished panels provide absorption required to create an acoustically correct space. Available in 1" and 2" NetWell Noise Control sound panels in BLUSH finish provide a range of NRC values suited to any acoustical solution.

APPLICATIONS

- Schools/Universities
- Auditoriums
- Houses of worship
- Office spaces

ACOUSTICAL DATA

Sound Absorption Coefficients								
Octave Band Frequencies	125	250	500	1000	2000	4000	NRC	SAA
1" Wall Panel	0.01	0.24	0.71	0.99	1.06	1.05	0.75	0.76
2" Wall Panel	0.30	0.85	1.09	1.05	0.99	1.01	1.00	0.99
1" Ceiling Tile	0.80	0.89	0.82	0.96	1.03	1.10	0.95	0.95
2" Ceiling Tile	0.80	0.83	0.99	1.04	1.02	0.98	0.95	0.98

SPECIFICATIONS

Specifications can be downloaded from our website www.controlnoise.com or call us at **1.800.638.9355**

BLUSH PANEL PAINT

BLUSH Paintable Panels offers a breathable paint to apply to your BLUSH Paintable Panels. Our paint is offered in all Pantone colors and should be applied as recommended in our field painting instructions or call **1.800.638.9355**.

- Excellent acoustical performance
- Class A fire rated per ASTM E-84
- Type A mount (wall panels),
Type E-400 mount (ceiling tiles)
- Custom sizes and shapes

