



# VET Panels

## SEMI-RIGID ACOUSTICAL PANELS

Semi-Rigid **VET Panels** are the perfect economical solution for large rooms with sound reverberation issues where a suspended ceiling baffle is not a feasible option. They are easy to install against the walls using fender washers & screws. The VET Panels are custom made with a wide variety of finishes and sizes available.

### FEATURES:

- Low cost, economical panels
- Excellent acoustical performance
- Moisture-resistant PVC
- Custom sizes available
- Easy to install
- Stainless steel grommets available

### APPLICATIONS:

- Indoor Swimming Pools
- Animal hospitals & boarding facilities
- Manufacturing environments
- Multi-purpose rooms



## SEMI-RIGID ACOUSTICAL VET PANELS

### SIZING

VET Panels are available in custom sizes up to 4' x 10'.

### THICKNESS / SUBSTRATES

- Standard thickness: 2", 1.5 PCF semi-rigid fiberglass core
- Also available: 1.5" thickness, 1.6 PCF semi-rigid fiberglass core

### FINISHES

Various finishes are available, including:

- PVC
- Sailcloth – Ripstop Nylon
- Fabrics – Standard is Guilford of Maine FR701-2100

### EDGE DETAIL

Stitched

### SUBSTRATES

Various options are available, including:

- 1.5 # PCF Semi-Rigid Fiberglass Core

### FIRE RATING

All components shall have a Class A fire rating per ASTM E-84

### MOUNTING OPTIONS

Nickel or stainless steel grommets

### ACOUSTICAL PERFORMANCE

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	SABINS
2" Thick (PVC)	1.94	4.68	11.61	11.84	6.04	2.66	8.54
2" Thick (PVC) Wall Mount	0.38	0.82	1.19	0.74	0.32	0.14	0.75
1½" Thick (Sailcloth)	1.37	4.86	9.21	13.55	8.39	4.70	9.0
1½" Thick (Fabric)	1.95	6.8	13.2	17.0	17.4	17.2	13.6

Tested as Type "J" Mount



#### SPECIFICATIONS:

Visit [www.controlnoise.com](http://www.controlnoise.com)  
or call **1.800.638.9355**

**NW**  
**NetWell**  
NOISE CONTROL