

SPEC DATA SHEET



NetWell Tapestry Banners are the perfect economical solution to reverberation issues for large spaces. They are easy to install horizontally with the ceiling via grommets or aluminum stiffener bars. Spacing the distance of the fixed ends will control the droop height. The Tapestry Banners are custom made with a wide variety of finishes and sizes available.

FEATURES:

- **APPLICATIONS:**
- Low cost, economical banners
- Excellent acoustical performance
- Stitched edges for extra durability
- Custom sizing
- Easy to install
- Wide variety of finishes

- Gymnasiums
- Sports venues
- Concert arenas
- Shopping centers

TAPESTRY ACOUSTIC BANNERS

SIZING

Custom sizes up to 4' x 20'.

THICKNESS / SUBSTRATES

Standard thickness: 2", 1.5 PCF fiberglass core

FINISHES

Various finishes are available, including:

- PVC (solid & perforated one side available)
- Sailcloth Ripstop Nylon
- Fabrics Standard is Guilford of Maine

EDGE DETAILS

Stitched

MOUNTING OPTIONS

Nickel grommets (aluminum stiffeners and washer plates also available)

SUBSTRATES

Various options are available, including 1.5 PCF

FIRE RATING

All components shall have a Class A fire rating per ASTM E-84

ACOUSTICAL PERFORMANCE

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2К	4K	NRC
2" w/ PVC Finish	0.92	0.92	1.01	0.85	0.38	0.25	0.80
2" w/ PVC Perforated One Side	1.04	1.00	0.99	1.15	1.10	1.14	1.05
2" w/ Ripstop Nylon Finish	0.89	0.97	1.01	1.02	0.59	0.32	0.90



SPECIFICATIONS: Visit www.controlnoise.com or call 1.800.638.9355

