

FELT BAFFLE | PET Acoustical Ceiling Baffle

The superior acoustical ceiling baffle. FELT Baffles are constructed with two layers of 9mm Plex Board and a center air space for maximum sound absorption. Combine that with the benefit of our wide array of beautiful PET felt sound absorbing material, and you've got the perfect match to your acoustical needs.



FELT BAFFLE

SPECIFICATIONS

Standard Baffle Sizes (WxH): 48"x 12", 48"x 16", 48"x 24"

96"x 12", 96"x 16", 96"x 24"

Thickness: 2-3/4"
Weight: 1.5 lbs/SF

Fire Rating: Class A per ASTM E-84

HARDWARE OPTIONS

Product can be installed with your choice of either aircraft cable or threaded rod attachments.

FEATURES:

- Easy Install
- Choice of 34 Colors
- Lightweight and Easy to Handle
- Linear Layout
- Modern Design
- Excellent Acoustical Values
- 4' and 8' Lengths
- Custom Sizes Available


ACOUSTICAL DATA

Frequency (Hz)	125	250	500	1000	2000	4000	SABINS
2-3/4" Thickness	2.94	4.45	7.05	10.62	12.61	13.64	

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
2-3/4" Thickness	.38	.57	.90	1.36	1.61	1.74	1.10

Based on Baffle size 4' x 2' with Type "J" Mounting. Sabins are based on Sabins per Object, NRC is an equivalent number based on one face of one panel


INSTALLATION OPTIONS








Threaded Rod Attachment







FELT BAFFLE | PET Acoustical Ceiling Baffle

FELT BAFFLE

COMPOSITION:

- 100% Polyethylene Terephthalate (PET)
- 55% recycled content

ENVIRONMENTAL FACTORS:

- 100% recyclable
- Low VOC Emissions
- ASTM D5116
- LEED MRc4



FINISHES







